

**iocare**



**iM 7** Vet Monitor

# iM 7 Vet Monitor



- Features:**
- Elegant design small size, much more portable;
  - 7 inches high resolution color TFT display;
  - Large font display;
  - User friendly interface, easy to operate;
  - Arrhythmia analysis and S-T segment analysis;
  - Static sound design, provide you quite and clean;
  - Rechargeable battery up to 4 hours continuous working;
  - Network connection with Central Monitoring System.

## Specifications:

### ECG

Lead Mode: 3/5 lead  
Lead Selection: I, II, III, AVR, AVL, AVF, V  
Measuring Range: 15 ~ 350 bpm  
Gain: 2.5mm/mV, 5mm/mV, 10mm/mV, 20mm/mV  
Sweep speed: 12.5mm/s, 25mm/s, 50mm/s  
Accuracy:  $\pm 1\%$

### SPO2

Range of measurement: 0~100%  
Resolution: 1%  
Accuracy: At 70~100%,  $\pm 2\%$   
Pulse rate measuring range: 20~254bpm  
Pulse rate accuracy:  $\pm 3$ bpm

### RESP

Measurement range: Adult 0-120 bpm  
Resolution: 1bpm  
Accuracy: 7 ~ 150bpm.  $\pm 2\%$

### TEMP

Measurement Range: 0-50°C  
Accuracy:  $\pm 0.1$   
Channel: 2-channel

### NIBP

Method: Automatic oscillometry  
Measuring range: 10~280 mmHg  
Resolution: 1 mmHg

## Accessory:



ECG Cable



NIBP Cuff



SpO2 Sensor



Probe for Temperature

**Shenzhen Biocare Electronics Co., Ltd.**



Add: Floor 6, Main Building, High-tech Innovation Park Baoan, Shenzhen, 518102, P.R.China

Tel: +86 755 27960641

Fax: +86 755 27960643

E-mail: sales@biocare.com.cn

<http://www.biocare.com.cn>